

[LATTICE PRO]

ANGLE ADJUSTABLE
SPOT TRACK LIGHT



5
YEAR
PRODUCT
WARRANTY

W
WATTAGE
SWITCHABLE

4
ANGLE
12°~60°

Description

Adjustable angle track lights allow you to direct the light exactly where you need it. This flexibility is particularly useful in spaces where the lighting requirements may change, such as galleries, retail stores, or art studios. User can easily create different lighting effects by adjusting the angle of the light beam. This allows you to highlight specific objects or areas in a room, creating a visually appealing and dynamic lighting design.



Key Features

- The Angle Adjustable Spot Track Light
- 12°~60° Angle Adjustable
- 24w | RA:80
- Warranty: 5 years | Lifud Driver
- Input Voltage: 200-240Vac PF>0.9 | THD<20%
- 6 Powers dipswitch
- FLICKER-FREE



Specification

Optical Parameters

CCT	3000K/4000K/5700K/6500K
CRI(Ra)	80
SDCM	6 (@3000K~5000K)
UGR	<15
Beam angle	12°~60° Angle Adjustable
Body Color	White/Black
Material	Lens: AL-Reflector
	Structure: aluminum
	Driver: Lifud CC

Lifetime

Warranty	5 years
L70B30	100,000+ hours
L80B10	80,000 hours
L90B10	50,000 hours
Driver failure rate	0.2% per 5000 hours
maintenance	Optical module sealed for life; no internal cleaning required


Electrical Parameters

Dimming	-
Input voltage	220-240Vac 50/60Hz
PF	0.95
PE	0.88
Over load/short Circuit	Protection
Driver Connection	Fixed
Hi-pot Test Range	SELV Isolated Driver, 3750Vdc/5mA/60S

Installation Information

"Average ambient temperature"	" Average ambient : +25 °c Operating temperature range: -10 to +40 °C"
Ceiling type	Track System 3-Phase/Circuit 4-Wire track
Light source	Non-replaceable LED module
IP	Total lamp IP20
IK	IK02

Model List



Model	Size(mm)	Power(w)	LPW(lm/w)	Lumen @CRI80 4000K 3000K	
TL-24W-AD	ø75x160	24	72	1728	1590

Model	"LED Q'ty"	"LED Class"	Package CTN Ctn Size(mm) G.W kg N.W kg			Q'ty CTN 40HQ
TL-24W-AD	1	P190RA90	460x330x380	12.30	10.80	20 20000

Dimensional Drawing

